OFTM-FB104P

10.4" Flat Bezel Open Frame PCAP Touch Monitors



Overview

The open frame touch monitors include bezel-free & flat bezel types with PCAP or resistive touch technology, which delivers an industrial & reliable solution with outstanding image clarity and accurate touch response that is cost-effective for OEMs and systems integrators. Embedded eye-catching and rugged bezel with flush front finish structure delivers flat design with high durability and scratch & water resistance. It is available in a wide range of sizes (7" to 55"), offering the versatility for embedded kiosk applications from self-service, gaming, industrial automation to digital signage & healthcare.

Features

- Touch thru glass enabled with PCAP supports thickness up to 5mm
- Full flat design with sturdy aluminum front bezel and metal enclosure
- IP65 (front) for water and dust protection; Flexible mounting in any table, kiosk, or cabinet design

Specifications

Panel	
Diagonal Size	10.4"(4:3), 26.42cm, Active matrix TFT LCD (LED)
Active Area (mm)	213.1 mm x 160.3 mm
Resolution	800 x 600
Viewing Angle	Horizontal: 85° or 170° total / Vertical: 85° or 170° total
Number of Colors	16.7 million
Brightness (typical)	Panel: 300 nits / With PCAP Touch: 265 nits
Response Time-total	25 msec typical
Contrast Ratio	800:1
Input Video Frequency	Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz
Touch	
Touch Technology	PCAP (Projected Capacitive) - 10 Touch Capacity
Surface Treatment	Water, Dust & Vandal proof, Anti-glare; Anti-fingerprint, Anti-smudge, Anti-bacterial (opt.)
Supported OS	Windows / Android / Linux / Mac
Interfaces / Connectors / Controls Video Interfaces VGA x1 / HDMI x1 / DVI x1 (opt.) / Display Port x1 (opt.) / USB x1 for Touch; HDCP: Yes	
video interideo	TOTAL TIDENT ALT TOTAL (Optin)

Interfaces / Connectors / Controls	
Video Interfaces	VGA x1 / HDMI x1 / DVI x1 (opt.) / Display Port x1 (opt.) / USB x1 for Touch; HDCP: Yes
Connectors & Controls	Audio Mini jack x1 / DC x1; 5 OSD buttons
Power	Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 10W typical, 1.2W sleep, 0.5W off
Mechanical	Product Dimensions: 267.5 x 214 x 39.2mm / Weight (Unpacked / Packed): 4 / 5 kg (2pcs) Box Dimensions: 445 x 390 x 190mm (2pcs) / VESA Mounting: 75 x 75 / 100 x 100mm
Environmental	Operating / Storage Temperature: -10°C to 60°C / -20°C to 60°C
Accessories	Power adapter/cable, HDMI/VGA/Touch USB cable, wall mount / table stands w/screws (opt.)
0.41	MTDE / Warranty / David Colory 50 000 hours demonstrated / 4 year / silver or block

MTBF / Warranty / Bezel Color: 50,000 hours demonstrated / 1-year / silver or black **Others**

Ready for Use: 24/7